

# 3M™ Dual ECAM EVOL D5-20 mm for BPEO



Dual ECAM EVOL D5-20 mm for BPEO

The ECAM cables entries for the BPEO closures have evolved to their EVOL generation.

The new system is designed for fast & practical installation with minimum specific tooling (only Torx™ screwdriver is required)

The ECAM concept, unique in the market, allows for the preparation of the cable entry on to the cable away from the closure. Once complete the completed cable entry can be quickly plugged in to the front side of the closure

The dual ECAM is located within the oval port of the front side of the BPEO closure range. The oval port of the BPEO closure is delivered with a plug that also can accept 2 single ECAM S4-12

### Content of the Kit\*



- 1 double cable lead-in joint,**
- 1 mastic strip,**
- 1 mastic cord,**
- 1 two-part conduit body,**
- 1 cleaning pad,**
- 2 tightening plates with screws**
- 2 sets of marked flanges for Ø 5 mm to Ø 20 mm.**

### Features

- ECAM design
- ECAM Concept
- Limited number of parts
- Components for diameter from 5 to 20 mm

### Benefits

- Can be used in all BPEO closure oval ports D20.
- Cable preparation away from the closure – Plug on front side – Secure with locking fork
- Easy to assemble – Minimum training
- Cover cables range for transport & distribution networks

## Specification

Dual Ecam EVOL D5-20



Cable Diameter from 5 to 20 mm

Water tightness = IP68

Strain Relief = 100 Kgs for central , lateral and soft strength members

## Ordering Information

## Ref. No.

BPEO Dual ECAM Kit D5-20 Evolution

N721130A

## BPEO Front Sides with D5-20 ports

## Ref. No.



BPEO Size 1



BPEO Size 2



BPEO Size 3

PORT D20 for Dual ECAM S4-20



FDP, CDP & EDP front side



501715




501488



501489

BDP Front side



501493

501496

### Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application.

All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law.

3M is a trademark of the 3M Company.



3M Communication Markets Division  
 3M United Kingdom Plc  
 3M Centre  
 Cain Road  
 Bracknell  
 Berkshire RG12 8HT  
 Internet: [www.3M.com](http://www.3M.com)

3M Communication Markets Division  
 3M Ireland Limited  
 Iveagh Building,  
 The Park,  
 Carrickmines,  
 Dublin 18 | Ireland

Rights reserved to make technical alterations.  
 Edition 07-401-26300 Index b-UK