



## Main

Range of product	Altira
Range	Altira
Product or component type	Socket-outlet
Device presentation	Mechanism
Number of power socket outlets	3 2P + E French
Outlet standard description	Pin earth
Socket additional information	Red tamperproof Shuttered
Colour tint	Red (RAL 3000) cover plate

## Complementary

Product destination	Fixing frames
Range compatibility	OptiLine 45 OptiLine 70 with Altira adaptor
Ground lug position	Slanted 45° position
Rated current	16 A - 250 V - AC - 50/60 Hz
Number of modules	6 modules
Fixing mode	Clip-in
Connections - terminals	Screwless terminals
Number of cables	4 x 1.5...2.5 mm <sup>2</sup> for rigid cable(s) 4 x 1.5...2.5 mm <sup>2</sup> for solid stranded cable(s)
Material	PC for mechanism cover
Surface treatment	Antibacterial
Surface finish	Satin
Standards	EN 60529 EN 62262 IEC 60884-1 NF C 61-314
Height	45 mm
Width	135 mm
Depth	39 mm
Product weight	0.123 kg

## Environment

ambient air temperature for operation	5...50 °C
ambient air temperature for storage	-15...60 °C
IK degree of protection	IK02
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid Hydrogen peroxide (H2O2)
environmental health and issues	Halogen free

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0201 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------