



Main

Range of product	OptiLine 45 OptiLine 50 OptiLine 70
Cabling installation system	Pole Post
Product or component type	Floor feeder
Type of pole	One installation box One-sided Two installation boxes Two-sided
Type of post	One-sided Two-sided
Colour tint	Grey RAL 7030
Quantity per set	28 m

Complementary

Pole/post surface finish	Anodized Powder coated
Pole fixing mode	Tension-mounted
Fixing mode	By screws
Material	PVC (polyvinyl chloride)
Length	2000 mm
Height	18 mm
Width	75 mm

Environment

standards	EN 50085-1 : 2005 NF C 68-102
ambient air temperature for operation	-25...60 °C
IP degree of protection	IP30

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0709 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.